

TROOPER S₃ SRC WR

Product Reference Trooper
ENISO20345:2011 S₃ SRC WR
Sizes 38-48
Weight (s. 41) 700gr.



Model description: leather + cordura shoe, Phylon/rubber sole, composite toe cap, puncture resistant SJ Flex midsole, Coolmax lining + waterproof membrane, ergonomic breathable SJ Hybrid, metal free

Application areas: military, security, police force

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend cleaning them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: composite toecap resistant to a shock of 200J and compression resistance of 1100N	Impact resistance	Mm	16.5	>14
		Compression resistance	Mm	20	>14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	29	>20
Upper	leather, black	Permeability to water vapor	Mg/m2 hour	4.18	>0,8
	Thickness 1,6 – 1.8 mm	Permeability coefficient	Mg/cm2	39	>15
Lining	Coolmax lining + waterproof membrane	Permeability to water vapor	Mg/cm2 hour	3.6	>2
Insole	Ergonomic breathable SJ Hybrid	Abrasion resistance	Cycles	PASS	>51200
Outsole	Antistatic Phylon/rubber	Abrasion resistance (volume loss)	Mm3	70	<150
	Shock Absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	1.2	<+12
	SRC Slip resistance (SRA+SRB)	Slip resistance on ceramic tile (SRA)	-	0.45 0.41	Heel: 0.28 Flat: 0.32
		Slip resistance on steel floor (SRB)	-	0.23 0.19	Heel: 0.13 Flat: 0.18
		Coefficient of adhesion of the outsole	N	4.7	>4N

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.